

# Apt-Cacher-NG User Manual

---

Apt-Cacher NG is a caching proxy for software packages which are downloaded by Unix/Linux system distribution mechanisms from mirror servers accessible via HTTP.

This manual provides an overview of Apt-Cacher-NG's features and a walk through the required configuration steps for server administrators and users of the proxy.

# Contents

---

|   |    |
|---|----|
| Chapter 1: Introduction                       | 4  |
| Chapter 2: Running apt-cacher-ng              | 5  |
| Chapter 3: Basic Configuration                | 6  |
| 3.1 Server Configuration                      | 6  |
| 3.2 Client Configuration                      | 6  |
| Chapter 4: Advanced Server Configuration      | 7  |
| 4.1 Vocabulary                                | 7  |
| 4.2 Configuration file types                  | 7  |
| 4.3 Repositories and URL mapping              | 8  |
| 4.3.1 Writing Remap-... configuration         | 9  |
| 4.3.2 Special tricks and additional notes     | 9  |
| Chapter 5: Security                           | 11 |
| Chapter 6: Distribution specific instructions | 12 |
| 6.1 Debian and Ubuntu                         | 12 |
| 6.2 OpenSUSE                                  | 12 |
| 6.3 Fedora Core                               | 12 |
| 6.4 Arch Linux                                | 12 |
| 6.5 Sourceforge mirror network                | 12 |
| 6.6 Cygwin mirrors                            | 13 |
| 6.7 Limited expiration                        | 13 |
| Chapter 7: Maintenance                        | 14 |
| 7.1 Manual cache cleanup                      | 14 |
| 7.2 Automated cache cleanup                   | 15 |
| 7.3 Removal of distribution releases          | 16 |
| Chapter 8: HOWTOs and FAQ                     | 17 |

|  |    |
|--|----|
| 8.1 Package import . . . . .   | 17 |
| 8.2 Cache overview . . . . .   | 18 |
| 8.3 Access control and inetd usage . . . . .   | 19 |
| 8.4 JIGDO usage . . . . .  | 19 |
| 8.5 Avoid use of apt-cacher-ng for certain hosts . . . . .                                 | 20 |
| 8.6 Avoid caching for certain domains or certain file types . . . . .                      | 20 |
| 8.7 How to make big download series faster . . . . .                                       | 20 |
| 8.8 How to import DVDs or ISO images . . . . .   | 20 |
| 8.9 How to integrate DVDs or ISO image data . . . . .                                      | 20 |
| 8.10 How to execute commands before and after going online? . . . . .                      | 21 |
| Chapter 9: Troubleshooting . . . . .   | 22 |
| 9.1 Debugging . . . . .  | 22 |
| 9.2 Problem: regular expiration action reproducibly aborts . . . . .                       | 22 |
| 9.3 Problem: download fails with 503 ... status message . . . . .                          | 22 |
| 9.4 Problem: <i>apt-get</i> freezes when downloading files . . . . .                       | 23 |
| 9.5 <i>apt-get</i> reports corrupted bzip2 data . . . . .                                  | 23 |
| 9.6 Problem: <i>apt-cacher-ng</i> refuses to start with "Address already in use" . . . . . | 24 |
| Chapter 10: Known Bugs and Limitations . . . . .   | 25 |
| Chapter 11: Contact . . . . .  | 26 |

# Chapter 1: Introduction

---

apt-cacher-ng attempts to achieve the same goals as related proxies - it acts as a proxy which is used by clients in the local network to share the data that has been downloaded. It monitors the state of packages and is capable of merging downloads of the same packages from different locations (real or simulated).

The package reuses many ideas behind the other famous proxy, its predecessor apt-cacher 1.x (which has been written in Perl). In contrast to apt-cacher, other aspects have been declared as primary targets during the development of apt-cacher-ng:

- lightweight implementation - allow the use on systems with low memory and processing resources
- internal (native) threading - avoiding process fork'ing wherever possible, avoiding kludges for pseudo-thread synchronization, avoiding excessive use of hidden file system features for internal operations
- real (effective) support of HTTP pipelining, therefore a native client with native stream control has been developed. The nice side effect is the reduction of resource overhead and minimization of possible points of failure
- avoiding featurities where they cause too much bloat and the functionality can be provided by native OS features
- reliable but efficient content merging in the local package pool, avoiding delivering of wrong data.

As with apt-cacher, explicit tracking of dynamically changed and unchanged files is established, and the use in non-Debian environment should be supported.

Long story: Not all goals have been achieved. The initial plan of using background databases to merge any download from any arbitrary location has been dropped because of complexity and performance considerations, reliable heuristics could not be found either. Instead, a semi-automated solution has been created which used machine-parseable files with mirror information, like the one available for Debian mirrors in Debian's CVS repository.

## Chapter 2: Running apt-cacher-ng

---

Run "build/apt-cacher-ng -c conf" when configured where conf is the configuration directory. See section 4.2 for details on possible and required contents of this directory.

Most options from the configuration file can also be passed through command line parameters. Just append them with the same format as in the configuration file but without separating spaces inside, e.g.

```
Port:4855
```

For convenience, the colon can also be replaced with the equals sign and letter case does not matter, so this is also possible:

```
port=4855.
```

# Chapter 3: Basic Configuration

---

## 3.1 Server Configuration

Unlike some rumors on the internet tell people, there should be no need for exhausting configuration work to just test apt-cacher-ng and run it with default parameters. It's actually designed to bootstrap its working environment without additional help.

The package setup scripts used by distributions should already prepare working initial settings for apt-cacher-ng. Check the file `/etc/apt-cacher-ng/acng.conf` file where most settings are explained. For the beginning they should not be changed, the only interesting setting present there is the TCP port. See Advanced Server Configuration for details.

## 3.2 Client Configuration

From the client side, apt-cacher-ng can be used as drop-in replacement for apt-cacher. The same rules apply, e.g. Debian/Ubuntu users should EITHER:

- Specify the caching machine as HTTP Proxy for APT, e.g. putting a line like the following into a file like `/etc/apt/apt.conf.d/02proxy`:

```
Acquire::http { Proxy "http://CacheServerIp:3142"; };
```

OR:

- Replace all mirror hostnames with cachinghost/hostname in `sources.list`, so

```
deb http://ftp.uni-kl.de/debian etch main
```

now would become:

```
deb http://192.168.0.17:3142/ftp.uni-kl.de/debian etch main
```

*(assuming that CacheServerIp is 192.168.0.17 and the service port is 3142).*

Mixing both configuration methods is not recommended and will lead to obscure APT failures in most cases.

Additionally, leading path component containing "apt-cacher/" or "apt-cacher?/" might be ignored by the server during the URL processing. This is intended behavior and exists to maintain backwards compatibility to `sources.list` entries configured for early versions of Apt-Cacher (based on CGI technology).

# Chapter 4: Advanced Server Configuration

---

## 4.1 Vocabulary

This chapter introduces some terminology which is needed to understand the functionality of apt-cacher-ng; it's recommended to understand it before continuing with the advanced configuration.

- "Backend": a text file consisting of a list of mirror URLs, one per line (a more complex RFC822-like format is also supported). Used for URL remapping; see section 4.3.
- "Volatile files": nothing to do with debian-volatile, volatile here only means that they are volatile, i.e. their contents are expected to be regularly changed on the server. For example, metadata pertaining to package files stored in a remote archive is classified as 'volatile'. This includes Packages, Sources, Release, Pdiff and similar files. Program messages sometimes refer to them as 'index files'.
- "Package files": files that contain software packages and other "solid" data: DEBs, source files for their creation (.tar.gz, .diff, .dsc), various metadata which is not subject to change after first appearance on the server.
- "Configuration line": one single line in the configuration file. Some examples in this chapter may contain wrapped lines but should be stored as a single line in the configuration.

## 4.2 Configuration file types

By default, the /etc/apt-cacher-ng directory (or the one specified with program options) contains all config files, HTML page templates, the stylesheet and other text-based support files used by apt-cacher-ng. The contents may vary depending on the installation of apt-cacher-ng, refer to the package documentation for Linux Distribution packages.

There are few certain file types distinguished by apt-cacher-ng:

1. Main configuration files:

\*.conf files are assumed to contain configuration directives in the form of "key: value" pairs. The package comes with a commented example configuration file. apt-cacher-ng reads all files matching \*.conf in alphabetical order and merges the contents. For options documentation, see commented example file shipped with apt-cacher-ng (conf/ directory in original source).

2. URL lists and remote repository list files. The file names are arbitrary, no special suffix is expected. They are included during processing of configuration files and can contain data in one the following formats:

- simple text files with one URL per line (the URL should point to the base directory of

the repository, e.g. "http://ftp.de.debian.org/debian/"). An URL must start with http:// and should end with a slash

- an RFC822-like format, with lines like 'Site: <hostname>' and 'Archive-http: /base/directory/of/repository/'. Optional fields are also used in this remapping descriptions to add more possible variants (Alias, Aliases, X-Archive-http:) of the URLs to the lookup list
3. Various support files used for the configuration web interface, named like \*.css and \*.html.
  4. \*.default files are used in some rare cases as replacement for list files having the same name without .default suffix.
  5. \*.hooks files specify custom actions which can be executed upon connection/disconnection (see section 4.3.2 for details).

### 4.3 Repositories and URL mapping

With the most simple configuration, apt-cacher-ng will act almost like an ordinary HTTP proxy with improved caching behaviour. When files are requested, they are downloaded from a remote location specified in client's request and are stored in a unique way.

However, for some use cases it can be beneficial to specify additional rules to achieve further improvements, e.g. in order to detect and prevent avoidable downloads, to reduce space requirements for the cache directory or simply hide real download locations from the APT clients.

These modifications are generally achieved by two strategies, *Merging* and *Redirection*, which are configured in a context of a specified cache *Repository*. The configuration for them is created using one or multiple *Remap-...* configuration directives (see below).

#### *Merging:*

"Merging" of incoming requests can be done if some subdirectories of the remote servers are considered equal where the last part of the remote file path after some directory leads to the same file content. When specified, the internal cache content is shared and the live download stream is shared. The configuration work consists of setting an "equality list" containing a set of URLs representing the base directories (like `http://ftp.debian.org/debian` and `http://ftp.uni-kl.de/pub/linux/debian`).

#### *Redirection:*

With redirection, client requests cause a download from a remote location which is different from what clients requested and believe to receive from. Redirection is an optional feature; if used, it's configured by one or multiple URL(s) pointing to target servers. The URL(s) must include a directory spec which matches the directory level of the URLs in the *Merging* URL(s), for example all ending with `/ubuntu/` for usual Ubuntu mirror URLs. If redirection is not used (i.e. the target URL list is empty) the original URL from client's request is used to get the data.

#### *Repository:*

A (cache) repository is the internal identifier which declares the scope in which *Merging/Redirection* specs are applied. It also represents the name of an internal cache subdirectory.



### 4.3.1 Writing Remap-... configuration

When use cases for merging/redirection are identified and a repository name is chosen, these components are written into configuration directives starting with `Remap-` which follow the simple syntax:

```
Remap-RepositoryName: MergingURLs ; TargetURLs
```

The repository name is a symbolic name which should be chosen carefully and should not be changed afterwards, otherwise the data might become inaccessible for clients until the files are extracted and reimported semi-manually. Internally, this string shares the namespace with host names and/or top directory names of other URLs. Name collisions can cause nasty side effects and shall be avoided. Recommended names are made up from alphanumeric or URL-friendly characters it also should not be associated to a real hostname. Examples for good names: `archlinux-repo`, `debianlocal`; examples for bad names: `fedora.example.com`, `_very&weird`.

The `TargetURLs` part is optional (see `Redirection` description above). If multiple targets are specified, the order of servers here defines in which order they are preferred (see also the `NetworkTimeout` option and additional notes below).

Both URL lists contain simply URLs separated by spaces. The strings must be properly URL-encoded. Since all URLs are assumed to belong to `http://` protocol and point to a remote directory, the `http://` protocol prefix and trailing slashes are optional. There is no hard limit to the number of URLs. However, for readability reasons it's recommended to put them into separate list files (see section 4.2) and specify the particular list files with tags like `file:urlsDebian.list` instead of writing them into a single line. Raw URLs and `file:...` lists can be mixed.

Fully configured Remap lines can look like:

*Example I:*

```
Remap-  
debrep: ftp.de.debian.org/debian http://ftp.at.debian.org/debian
```

for the use case: small home network, clients have `de...` or `at...` servers in their `sources.list` files and use `acng` as HTTP proxy. Now the files are still downloaded from `at...` or `de...` mirrors depending on the user request, but already cached data is served to both, `at...` and `de...` users.

*Example II:*

```
Remap-  
ubuntu: file:ubumir.lst ; 192.168.17.23/pu ca.archive.ubuntu.com/ubuntu
```

for the use case: small home network, clients have various Ubuntu mirrors (which are listed in `ubumir.lst`) in their `sources.list` files and use `acng` as HTTP proxy. All requests are redirected to a mirror in the `/pu` directory of some local machine. When that machine is down, Canadian public server is used instead.

### 4.3.2 Special tricks and additional notes

There are some implementation details (partially explained above) and some configuration options related to repository settings which should be mentioned explicitly.

The internal cache directory tree follows the URL requests from the clients unless modified by Remapping rules. For proxy-style configuration on the user side, it is always the hostname of the requested URL. But if clients access the apt-cacher-ng server like a regular mirror (not using APT's proxy config) then it's just passed as regular directory name. And at this point, it's possible to use Remapping constructs to access random remote locations while the client assumes to download from a subdirectory of apt-cacher-ng (as http server). This is configured by simply using `/some/directory/string/` instead of URLs in the `Merging` list to let your clients download from `http://acngserver/some/directory/string/...` paths.

If multiple `Remap-` lines for the same `Repository` are specified, the contents of both URL lists are merged.

On some restricted networks, it may be needed to enforce the user of predefined mirrors. If the `ForceManaged` option is set, only requests to URL matched in some `Remap-...` config is allowed.

Sometimes, it may be needed to execute a system command before connection to certain machines is established. This is possible by associating them with a repository declaration, i.e. by storing a file called like `repositoryname.hooks` in the main configuration directory. It can contain `PreUp`, `Down` and `DownTimeout` settings. `PreUp/Down` are executed by the system shell and it's up to administrator to make sure that no malicious code is contained there and that the execution of that commands does not significantly delay the work for other apt-cacher-ng users.

If the `Redirection` part contains multiple URLs, the server prefers to use them in the order of appearance. On success, the first target is used all the time, and so this should be the preferred mirror. "Success" means getting a started download or a non-critical failure in this context. A "404 File not found" status is not a critical failure since APT (client) can expect it while checking for existence of remote files and change its behaviour accordingly.

## Chapter 5: Security

---

Like many data storing daemons with predictable filenames, apt-cacher-ng is vulnerable to symlink attacks and similar malicious actions. Therefore, the user must make sure that the cache and log directories are writable only to the user account under which apt-cacher-ng is executed on.

As to the program internal security, apt-cacher-ng has been developed to care about a certain level of attacks from internal users as well as from malicious outside hosts. However, no guarantees can be made about the security of the program. It's recommended to run apt-cacher-ng under a system account which has no access to any system files outside of the cache and log directories. Refer to the manuals of the administration utilities of your distribution (like start-stop-daemon) to create the required configuration.

If relaxed permissions are required, e.g. to make files group-writable, this can be established through the appropriate use of the `umask` command in the startup scripts of apt-cacher-ng (see `/etc/default/apt-cacher-ng`, for example) and the sticky bit on the cache directories (see `chmod(1)` manpage for details).

## Chapter 6: Distribution specific instructions

---

### 6.1 Debian and Ubuntu

Use as is. Report bugs using reportbug (Debian) or to Launchpad (Ubuntu).

### 6.2 OpenSUSE

Server can be used as is with limited expiration (see below, and see `INSTALL` file for compilation hints). The merging mode (multiple servers mapped into the same repository) is not preconfigured in the example configuration. This is object to research, competent support is required.

Clients can configure `apt-cacher-ng` as central proxy in Yast ("Network devices"/"Proxy" tab). If this is not desirable then each software source can be edited to be redirected through the server. This can be done in the Software Installer view of Yast2, see menu Configuration/Repositories. To edit them quickly, switch to URL editing mode and insert `host:port/` (of the `apt-cacher-ng` server) between `http://` and the source server name.

### 6.3 Fedora Core

Attempts to add `apt-cacher-ng` support ended up in pain and the author lost any motivation in further research on this subject.

### 6.4 Arch Linux

Mostly usable. The mirror structure design has been identified by trial-and-error and the regular expressions might need some tuning by experts.

The installer seems to have no way to specify a dedicated proxy but it's possible to edit the source URL and insert `host:port` part into it `host:port/`. The `pacman` mirror list can be modified the same way.

Expiration code should work in the basic mode (index data is extracted from `*.db.tar.gz` files). File checksum checking mode might also work (untested). The example configuration contains a preconfigured list of mirrors which can be rebuilt with the `Makefile` if needed. The preferred backend server can be specified like with other distributions (see above for details).

### 6.5 Sourceforge mirror network

Not a Linux distro but commonly used by those to download certain files. Therefore most mirrors can get unified access cache sharing the files in the same cache repository. Some `.exe` files there are never expired.

## 6.6 Cygwin mirrors

While not being a pure Linux distro it's mostly GNU and has a nice mirror setup. Proxy server can be used as is with limited expiration (see below). It can also be compiled and executed on Windows machines (see `INSTALL` file for details).

Clients need to specify the server as HTTP proxy in the `setup.exe` wizard, and then select only HTTP mirrors should be selected in the mirror list.

## 6.7 Limited expiration

The expiration code for Non-Debian/Ubuntu repositories is quite limited due to lack of manpower or know-how or refusal to implement bloated code like complete XML parser. For some distros, the support is limited to checks of the filename and no further validation is supported. Therefore, the extra validation of path location or file contents should NOT be turned on when running expiration with data from that distros in the cache, because good data may be deleted in this case.

# Chapter 7: Maintenance

---

There are few optional tasks that need to be executed by the administrator from time to time or during the initial configuration.

## 7.1 Manual cache cleanup

If a package is no longer downloadable by APT clients then its files are also not referenced in any volatile (index) file and can be removed. This rule also applies to most volatile files at the distribution level. I.e. the Release file references some Packages and Sources files or Diff-Index file, and those do reference most other non-volatile files (binary packages, source packages, index diffs, ...).

To run this cleanup action manually visit the report page in a browser and trigger the *Expiration* operation there.

There are different flags configuring the parameters of this tracking described below. Usually just the filename is sufficient to consider a file in the cache as a valid (downloadable) file. This is ok in most cases but sometimes leads to false positives, i.e. when another repository in the cache refers to a file with the same name but the reference to the original location is gone. On the other hand there can be cases where the assignment to different repositories happened by mistake and administrator would like to merge repositories later on.

For most files the checksum values are also provided in the index files and so the file contents can be validated as well. This requires reading of the whole cache archive to generate local checksums. It should also not be done when apt-cacher-ng is being used (file locking is not used here).

Usually it's necessary to bring various index files (Release,Sources,Packages,Index) in sync with the repository. This is necessary because apt works around the whole file download by fetching small patches for the original file, and this mode of operation is not supported yet by apt-cacher-ng (and might still be unreliable). When this synchronization fails, the index files might be incomplete or obsolete or damaged, and they might no longer contain references to some files in the cache. Abortion of the cleanup process is advisable in this case.

There is also a precaution mechanism designed to prevent the destruction of cache contents when some volatile index files have been lost temporarily. The results of cache examination are stored in a list with the date when the particular files became orphaned. The removals are only executed after few days (configurable, see configuration file) unless they are removed from this list in the meantime.

Parameters of *Expiration*:

*Stop cleanup on errors during index update step*

Index files update is done first, on errors the expiration will be interrupted.

### *Validate by file name AND file directory*

This option can be used to remove distribution stages. Example: to remove "oldstable" one just needs to delete the "Release" files in the cache and run *Expiration* with this option two times. There are some issues with this mode operation, see above for details.

### *Validate by file name AND file contents (through checksum)*

Checking file contents where possible, also attempt to detect incorrect file size information in the cached metadata. Note: the check results are stored only once, future calls without this option can overwrite the results again. Use action buttons (see below) to delete corrupted files after the scan.

### *Force the download of index files*

Sometimes it may be needed to redownload all index files, explicitly replacing the cached versions. This flag enables this behaviour.

### *Purge unreferenced files after scan*

Avoid the use of the orphan list and delete files instead. This option is dangerous and should not be used unless when absolutely no mistakes/problems can happen. Instead, it's possible to view the orphan list later and delete then (see below).

### *More verbosity*

Shows more information, e.g. each scanned file when used with some of the other options. This might result in a very large HTML page, making the watching HTML browser very slow.

In addition to the default scan run, there are some "Direct Action" buttons in the Web frontend. It's possible to see the temporary list of files that have been identified as orphaned (unreferenced), and it's possible to delete all files from that list immediately. To be used carefully!

## **7.2 Automated cache cleanup**

A script called `expire-caller.pl` is shipped with the package. This script effectively implements a HTTP client which operates like a human would do when running the expiration manually (see above). It can also extract the operator password and unix socket file path from the local configuration file. On Debian installations it is called by the file `/etc/cron.daily/apt-cacher-ng` so it should run automatically as daily cron task. The results are usually not reported unless an error occurs, in which case some hints are written to the standard error output (i.e. sent in cron mails).

The operator script can take some options from the environment, also see the cron script for details:

*ACNGIP=10.0.1.3*

The network address for remote connection may be guessed incorrectly by the operator script. This variable can specify an explicit target to connect to, e.g. the same IP as the one used by the clients (unless this network connection is somehow restricted in the local setup).

*HOSTNAME=localOrPublicName*

When an error occurs, the operator script most likely adds an URL to be opened for further investigation. The host name of in this URL can be customized, i.e. can be set to a public domain name representing the server as accessible from the administrator's machine.

### **7.3 Removal of distribution releases**

Sometimes it's needed to remove all files from a distribution, i.e. when a new release became Stable and older package files are still lying around. In perfect conditions the reference tracking described above should take care of it and remove them soon.

However, this solution will fail if the release files are still available on the server AND apt-cacher-ng learned their real location (i.e. the code name instead of not the release state name) and so they are refreshed during regular expiration.

After all, if the old release is no longer used by local cache users then the extra disk usage becomes a problem. This problem will go away after many months when the old release files are finally deleted on the servers, then the package expiration will start complaining for some days (the expiration delay) and only then the finally unreferenced files will be removed.

To speed up this process, the local administrator can remove the traces of the old distribution release from the archive. Either the top-level "Release" files, or even the whole index file trees relevant for certain releases.

To make this task easier, a "brutal" script called distkill.pl is shipped with apt-cacher-ng. It runs interactively, it scans the package directory and presents an overview of index file trees assumed to represent distro releases. Then it provides a command prompt to remove some immediately. The script should be used with extreme care! See section 8.2 for example of its output.



## Chapter 8: HOWTOs and FAQ

---

### 8.1 Package import

Already existing packages can be imported into apt-cacher-ng's cache pool instead of downloading them. There are some restrictions:

1. Don't try to import incomplete files. They will be refused since their contents cannot be checked against the archive metadata.
2. If possible, don't import symbolic links. Even if doing so, they should not point to other files inside of the cache and especially not to other files under the `_import` directory.

HOWTO:

1. Make sure that apt-cacher-ng has valid index files in the cache. This is the tricky part. To get them right, a client needs to download them through apt-cacher-ng once. Therefore:
  1. Configure the server and one client before doing the import. See above for instructions.
  2. Run "apt-get update" on client(s) once to teach ACNG about remote locations of (volatile) index files. In some cases this is not sufficient. See the note on APT below for a workaround.

2. Store copies of your `.debs`, `.orig.tar.gz`, ... somewhere in the `"_import"` subdirectory in the cache, ie. in `/var/cache/apt-cacher/_import/`. The files may be links or symlinks, does not matter. When done, apt-cacher will move those files to its own internal locations. Example:

```
cd /var/cache
mkdir apt-cacher-ng/_import
cp -laf apt-proxy apt-cacher /var/cache/apt-cacher-ng/_import
chown -R apt-cacher-ng apt-cacher-ng/_import
```

3. Visit the report page and trigger the import action there. Check the results, look for (red) error messages.
4. Check the `_import` directory again. All files that could be identified as referenced by archive metadata should no longer be there if they have been successfully moved. If some files have been left behind, check whether the client can use them, i.e. with "apt-cache policy ..." and/or checking checksums with `md5sum/sha1sum` tools. Probably they are no longer needed by anyone and therefore apt-cacher-ng just left them behind. If no, follow the instructions in 1 or do similar things for your distribution and retry the import operation. Setting the verbosity flag (see checkbox on the command-and-control page) can also help to discover the reason for the refusal to import the particular files.

NOTE: APT is pretty efficient on avoiding unnecessary downloads which can make a proxy blind to some relevant files. ACNG makes some attempts to guess the remote locations of missed

(not downloaded) files but these heuristics may fail, especially on non-Debian systems. When some files are permanently ignored, check the process output for messages about the update of Packages/Sources files. When some relevant package sources are missing there, there is a brute-force method for Debian/Ubuntu users to force their download to the client side. To do that, run:

```
rm /var/cache/apt/*cache.bin
rm /var/lib/apt/lists/*Packages
rm /var/lib/apt/lists/*Sources
```

on the client to purge APT's internal cache, and then rerun "apt-get update" there.

## 8.2 Cache overview

To get a basic overview of the cache contents, the distkill.pl script may be used. See section 7.3 for details and warnings.

```
# /usr/lib/apt-cacher-ng/distkill.pl
Scanning /var/cache/apt-cacher-ng, please wait...
Found distributions:
1. testing (6 index files)
2. sid (63 index files)
3. etch-unikl (30 index files)
4. etch (30 index files)
5. experimental (505 index files)
6. lenny (57 index files)
7. unstable (918 index files)
8. stable (10 index files)
```

WARNING: The removal action would wipe out whole directories containing index files. Select d to see detailed list.

Which distribution to remove? (Number, 0 to exit, d for details): d

Directories to remove:

1. testing:  
/var/cache/apt-cacher-ng/debrep/dists/testing
2. sid:  
/var/cache/apt-cacher-ng/localstuff/dists/sid  
/var/cache/apt-cacher-ng/debrep/dists/sid
4. etch:  
/var/cache/apt-cacher-ng/ftp.debian-unofficial.org/debian/dists/etch
5. experimental:  
/var/cache/apt-cacher-ng/debrep/dists/experimental
6. lenny:  
/var/cache/apt-cacher-ng/security.debian.org/dists/lenny  
/var/cache/apt-cacher-ng/debrep/dists/lenny
7. unstable:  
/var/cache/apt-cacher-ng/debrep/dists/unstable  
/var/cache/apt-cacher-ng/localstuff/debian/dists/unstable
8. stable:

```
/var/cache/apt-cacher-ng/debrep/dists/stable
Found distributions:
```

WARNING: The removal action would wipe out whole directories containing index files. Select d to see detailed list.

## 8.3 Access control and inetd usage

Filtering by client IP or hostname is not supported directly. However, an inetd daemon is shipped with the package which makes the use of tcpd possible. Installation is done in following steps:

1. compile the inetd bridge tool "in.acng", if not already done (check `/usr/lib/apt-cacher-ng`).
2. Edit apt-cacher-ng's configuration (acng.conf, for example), and set a path for a new file in a writable directory, like this:

```
SocketPath: /var/run/apt-cacher-ng/socket
```

3. Edit `/etc/inetd.conf` and add following line with appropriate path names and TCP port:

```
3143  stream  tcp  nowait  user  /usr/sbin/tcpd
      /usr/local/sbin/in.acng /var/run/apt-cacher-ng/socket
```

4. Edit `hosts.allow` and other files to configure ACLs for port 3143. See `tcpd(8)` and related manpages for further details.
5. Configure clients to use the alternative port (3143 in the example above).

## 8.4 JIGDO usage

It's possible to use apt-cacher-ng source with the jigdo-lite utility. There are some limitations, though:

- since many mirrors do not distribute the jigdo files (or even nothing from `cdimage.debian.org` at all), there is a high chance to be redirected to a such mirror when using the backend-mapped configuration. I.e. when user follows the official documentation and edits `wgetOpts` in the jigdo configuration, it will fail in many cases.
- apt-cacher-ng does not support `.template` files properly. They might be cached but will be expired (removed from cache), sooner or later.

But it's possible to feed jigdo-lite with the package contents from your mirror. To do that, first start jigdo-lite as usual, something like:

```
jigdo-lite http://cdimage.debian.org/.../...-DVD-1.jigdo
```

When asked about Debian mirror, enter something like:

```
http://proxy.host:3142/ftp.de.debian.org/debian/
```

i.e. construct the same URL as present in usual apt-cacher-ng's user's `sources.list`.

That's all, jigdo-lite will fetch the package files using apt-cacher-ng proxy.

## 8.5 Avoid use of apt-cacher-ng for certain hosts

Sometimes clients might need to access some remote side directly to do some non-file-transfer oriented work but still passing the data through configured apt-cacher-ng proxy. Such remote hosts can be marked for direct access in apt configuration, e.g. in `/etc/apt/apt.conf`:

```
Acquire::HTTP::Proxy::archive.example.org "DIRECT";  
//or Acquire::HTTP::Proxy::archive.example.org "other.proxy:port"
```

## 8.6 Avoid caching for certain domains or certain file types

Sometimes clients to download through apt-cacher-ng but the data shall not be stored on the harddisk of the server. To get it, use the `DontCache` directive (see examples for details) to define such files.

## 8.7 How to make big download series faster

Symptom: A common situation is a periodic download of hundreds of files through apt-cacher-ng where just a half is present in the cache. Although caching works fine, there are visible delays on some files during the download.

Possible cause and relief: the download from the real mirror gets interrupted while apt-cacher-ng delivers a set of files from the internal cache. While the connection is suspended, it times out and needs to be recreated when a miss occurs, i.e. apt-cacher-ng has to fetch more from the remote mirror. A workaround to this behaviour is simple, provided that the remote mirror can handle long request queues: set the pipelining depth to a very high value in apt.conf file or one of its replacement files in `/etc/apt/apt.conf.d/`. With something like:

```
Acquire::http { Pipeline-Depth "200"; }
```

there is a higher chance to get the server connection "preheated" before a stall occurs.

## 8.8 How to import DVDs or ISO images

First, it should be clear what is needed to be done. In order to integrate the packages from a DVD or ISO image, read on in section 8.9.

The situation with ISO files import is complicated. They are not supported by the cache and there is also no expiration mode for them. The feature might be considered for addition in some future release of apt-cacher-ng.

What is possible now is publishing a directory with ISO files using its web server mode, see `LocalDirs` config option for details.

## 8.9 How to integrate DVDs or ISO image data

Integrating package files from DVD or ISO images is not much different to the usual import operation, see above for instructions.

One possible way to get files into the `_import` directory is simply mounting it there:

```
mount -o loop /dev/cdrom /var/cache/apt-cacher-ng/_import
```

After running the import operation, the disk can be unmounted and removed.

A possible variation is import via symlinks. This can make sense when the space consumption must be reduced and the ISO image should stay on the server for a long time. To achieve this, the image should be mounted at some mount point outside of the `_import` directory, the state should be set permanently via an `/etc/fstab` entry (don't forget the `loop` option), then a symlink tree pointing to the mountpoint location should be created in the `_import` directory (something like `cp -as /mnt/image_sarge_01/pool /var/cache/apt-cacher-ng/_import`). The subsequent "import" operation should pick up the symlinks and keep them symlinks instead of making file copies.

## 8.10 How to execute commands before and after going online?

It is possible to configure custom commands which are executed before the internet connection attempt and after a certain period after closing the connection. The commands are bound to a remapping configuration and the config file is named after the name of that remapping config, like `debrep.hooks` for `Remap-debrep`. See `conf/* .hooks` or `/usr/share/doc/apt-cacher-ng/examples/* .hooks` files for details.

# Chapter 9: Troubleshooting

---

## 9.1 Debugging

Preliminary meanings of Debug option settings are:

- 0: No debug printing
- 1: Log file write buffers are flushed faster
- 2: extra information appears within usual transfer log
- 3: additional process information appears in apt-cacher.err
- 4: extra debug information is written to apt-cacher.err
- >=5: much more debug information written to apt-cacher.err (requires a recompilation of apt-cacher-ng binary with special debug flag(s), see section 9.4 for details)
- 11: like 5 plus all internal trace pointers are logged

Getting HTTP headers from apt-get works like this:

```
apt-get update -o Debug::Acquire::Http=true
```

## 9.2 Problem: regular expiration action reproducibly aborts

A quick investigation of action logs should help identifying the problem. A typical one is a mirror listed somewhere which is not reachable when expiration runs.

Unfortunately there is no simple and safe way to solve this. One method is setting the ExAbortOnProblems configuration variable, but this can destroy the whole cache if a bigger problem with index file occurs and this state remains unnoticed for many days until ExTreshold period (see configuration) is over.

Another way is listing the index files of the faulty mirrors to a special file. It needs to be stored as "ignore\_list" in the configuration directory and store one path name per line with paths relative to the cache directory, as seen in the error messages.

## 9.3 Problem: download fails with 503 ... status message

Code 503 usually represents an internal failure which could not be described correctly by other HTTP status codes. In the most cases it's caused by file system errors or incorrect cache directory setup, like files or directories with incorrect owner, missing write/read permissions for the effective user account or other system related exceptions like running out of disk space.

The log file `apt-cacher.err` located in the `LogDir` directory should document more details. In case it doesn't, setting the `Debug` config option to a higher value might reveal more

information.

Fixing permission problems shouldn't be a real challenge for system administrators. Usually, a command set like this should do the trick on Debian/Ubuntu systems, assuming that all group users should receive write access to the cache files:

```
chown -R apt-cacher-ng:apt-cacher-ng /var/cache/apt-cacher-ng
chmod -R a+rX,g+rw,u+rw /var/cache/apt-cacher-ng
```

## 9.4 Problem: *apt-get* freezes when downloading files

Solution: First, check:

- Free disk space and inode usage ("*df*", "*df -i*")
- Internet connection to the remote sites (browse them via HTTP, e.g. visiting <http://ftp.your.mirror>)

If nothing helps then you may have hit a spooky problem which is hard to track down. If you like, help the author on problem identification. To do that, do:

```
su -
# enter root password
cd /tmp
apt-get source apt-cacher-ng
apt-get build-dep apt-cacher-ng
cd apt-cacher-ng-*
make acng DEBUG=1
/etc/init.d/apt-cacher-ng stop
./apt-cacher-ng -c /etc/apt-cacher-ng logdir=/tmp foreground=1 debug=6
# (let apt-get run now, on timeouts just wait >> 20 seconds)
# stop the daemon with Ctrl-C
/etc/init.d/apt-cacher-ng start
# compress /tmp/apt-cacher.err and send it to author
chown -R apt-cacher-ng:apt-cacher-ng /var/cache/apt-cacher-ng
```

The value of debug can be varied to have different verbosity (see section 9.1 for more information about Debug levels). 11 is recommended for really weird problems.

## 9.5 *apt-get* reports corrupted bzip2 data

Symptoms: *apt-get* fails to run through "update" no matter what you do. And you may have get a message like this one.

```
99% [6 Packages bzip2 0] [Waiting for headers] [Waiting for headers]
bzip2: Data integrity error when decompressing.
    Input file = (stdin), output file = (stdout)
```

It is possible that the compressed file(s) have become corrupted. You can use the *-tvv* option to test integrity of such files.

You can use the ``bzip2recover'` program to attempt to recover data from undamaged sections of corrupted files.

```
Err http://debian.netcologne.de unstable/main Packages
Sub-process bzip2 returned an error code (2)
```

- This might be one of Apt's problem with insufficient handling of errors, i.e. passing incomplete files to bzip2 on premature connection termination. Retry the update and it might work.
- Another issue is more severe: old versions of apt-cacher-ng had a bug which could cause data corruption while resuming downloads however this problem appears only in unusual conditions. To make sure there are no broken files in your repository, run the Expiration task with content verification enabled, and also "immediate deletion" (or delete later after checking the list). See section 7.1 for details.

## 9.6 Problem: *apt-cacher-ng* refuses to start with "Address already in use"

Another service is already listening on the port which apt-cacher-ng is configured to use. This might be the apt-cacher daemon which used the same port number by default. To identify the daemon behind that process, use the fuser utility, executing it as root for IPv4 and IPv6 protocol versions. Example:

```
fuser -4 -v -n tcp 3142
fuser -6 -v -n tcp 3142
          USER          PID ACCESS COMMAND
3142/tcp:          xwwwfsd    17914 F....  xwwwfsd
```

(where 3142 is the port number from the apt-cacher-ng configuration file). To resolve the collision, reconfigure the other daemon or apt-cacher-ng to use another free port (and reconfigure the clients to use the new apt-cacher-ng port).



## Chapter 10: Known Bugs and Limitations

---

- Versions between 0.2.6 and 0.3.3 created broken X-Original-Source URLs in the .head files. The effects should be negligible.
- Only HTTP proxy authentication of the "Basic" type is supported at the moment
- Only HTTP HEAD and GET commands are supported properly. POST support is limited to the calls made by apt-listbugs and might garble some requests.
- Native HTTP redirection not supported (redirect hint passed through to client)
- Transparent proxy support not implemented yet
- See TODO file in apt-cacher-ng source for various other notes
- "Code 520824" (see below)

Few versions of apt-cacher-ng did lose some information about the original source of downloaded files. This has been unnoticed for many months, because the path resolution algorithm tries to use a file path components to guess the original URL, or guess the cache repository and then download from using this repository (backends definitions).

The good news is that the missing information is completed automatically when a file is redownloaded once (or resumed) through apt-cacher-ng. Static package files are usually not redownloaded, but the missing information is not relevant for them.

The bad news is that in some cases this might become a problem, particularly when an expiration/import task tries to refresh the index file which is stored inside of a (former) repository tree and the administrator has removed the backends definitions for this repository. When ACNG runs out of possible sources it reports "Code 520824" and refers to this text. However, the detection of this situation is still not perfect and in rare cases it's possible that messages about failed resolution of some hostname (identical with former cache repository name) will appear.

## Chapter 11: Contact

---

The planned features are listed in the file TODO. Don't hesitate to contact the author if you really need something not found there and you can explain the severity of your request.

To say thanks, visit <http://flattr.com/thing/51105/Apt-Cacher-NG>.

Please report any bugs found in apt-cacher (which are not obviously the complementary of missing features, see above).